STARKLER

GENERAL INDUSTRY

Hot water and multipurpose chemicals



APPLICATIONS

A versatile hose for high pressure cleaning operations and general discharge service using hot or cold water and many other fluids (see chemical resistance table for EPDM).

Suitable for all sectors: building and public works, industry, agriculture, etc.

ADVANTAGES

- Extremely resistant to ageing and atmospheric conditions.
- Wide range of operating temperatures (-30°C to +100°C).
- Wide range of diameters.
- Excellent mechanical properties.
- Resistant to many fluids.
- Attractive, well-finished appearance.
- Long service life.

TECHNICAL DESCRIPTION

Inner tube: EPDM, black, smooth.
Reinforcement: synthetic textile.
Cover: EPDM, black, smooth for ID from 12.7 to 25.4mm, fabric impression for ID from 30 to 38mm.
Temperature range: -30°C to +100°C.

STANDARD/APPROVAL

In compliance with ISO 1403 type 2 (except branding). ISO

12.7-25.4mm



and in opposite:



30-38mm



GENERAL INDUSTRY | STARKLER



ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (l) or min. order m
12.7 ±0.6	4	20.7 ±0.7	20	60	55	0.27	20	0060012	l
12.7 ±0.6	4	20.7 ±0.7	20	60	55	0.27	40	0060013	l
12.7 ±0.6	4	20.7 ±0.7	20	60	55	0.27	80	0060990	l
15.8 ±0.7	4.1	24.0 ±0.8	20	60	70	0.33	20	0060014	l
15.8 ±0.7	4.1	24.0 ±0.8	20	60	70	0.33	40	0060015	l
15.8 ±0.7	4.1	24.0 ±0.8	20	60	70	0.33	80	0060991	l
19.4 ±0.7	4.5	28.4 ±0.8	20	60	85	0.43	20	0060016	l
19.4 ±0.7	4.5	28.4 ±0.8	20	60	85	0.43	40	0060017	l
19.4 ±0.7	4.5	28.4 ±0.8	20	60	85	0.43	80	0060992	l
25.4 ±1.0	4.8	35.0 ±1.1	20	60	100	0.58	20	0060018	l
25.4 ±1.0	4.8	35.0 ±1.1	20	60	100	0.58	40	0060019	l
25.4 ±1.0	4.8	35.0 ±1.1	20	60	100	0.58	80	0060993	l
30.0 ±1.0	4.25	39.0 ±1.0	10	30	240	0.72	20	0200259	l
30.0 ±1.0	4.25	39.0 ±1.0	10	30	240	0.72	40	0200260	l
32.0 ±1.0	4.25	41.0 ±1.0	10	30	260	0.77	20	0123234	l
32.0 ±1.0	4.25	41.0 ±1.0	10	30	260	0.77	40	0123239	l
35.0 ±1.0	4.25	44.0 ±1.0	10	30	280	0.83	20	0200261	l
35.0 ±1.0	4.25	44.0 ±1.0	10	30	280	0.83	40	0200262	l
38.0 ±1.0	4.25	47.0 ±1.0	10	30	310	0.89	20	0123245	200
38.0 ±1.0	4.25	47.0 ±1.0	10	30	310	0.89	40	0070387	200

Tolerance on length: ±1% (ISO 1307 Standard).