

ASPIKLER N



CONSTRUCTION & INFRASTRUCTURE

Drain and sewer cleaning



APPLICATIONS

For sewer suction.

Also for suction or delivery of abrasive materials on stationary systems and for cassette applications on sewer cleaning vehicles.

ADVANTAGES

- ¹ High resistance to abrasive environment and abrasive transportation media.
- ¹ Suitable both for suction and pressure.

TECHNICAL DESCRIPTION

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile cords with embedded steel helix.

Cover: SBR/NR, black, fabric impression.

Temperature range: -30°C to +80°C.



 CONSTRUCTION & INFRASTRUCTURE			ASPIKLER N							
ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (1) or min. order m
100.0 ±1.0	8	116.5 ±1.5	6	15	0.9	450	4.3	20	0095016	1
100.0 ±1.0	8	116.5 ±1.5	6	15	0.9	450	4.3	40	0096724	1
102.0 ±1.0	8	118.0 ±1.5	6	15	0.9	450	4.38	20	5513565	1
125.0 ±1.2	9.5	144.0 ±1.5	6	15	0.9	550	6.3	20	0094152	1
125.0 ±1.2	9.5	144.0 ±1.5	6	15	0.9	550	6.3	40	5009671	1
127.0 ±1.2	9.5	146.0 ±1.5	6	15	0.9	550	6.39	20	5513566	1
150.0 ±1.2	10	170.0 ±1.5	6	15	0.9	650	7.77	20	5008847	1
152.0 ±1.2	10	172.0 ±1.5	6	15	0.9	650	7.87	20	5513567	1
Tolerance on length: ±1% (ISO 1307 Standard).										

Digital version



WWW.TRELLEBORG.COM/FLUIDHANDLING