

S 2096



OIL & GAS

Steam



APPLICATIONS

For heavy duty industrial cleaning and circulation of saturated and superheated steam in heating systems.

Used in the petrochemical, building, shipyard and chemical industry.

ADVANTAGES

- ¹ Multipurpose hose.
- ¹ Highly flexible.
- ¹ Very high temperature resistance.
- ¹ Chemical resistant.
- ¹ Durable and safe performance.
- ¹ Fulfills international standards.

TECHNICAL DESCRIPTION

Inner tube: EPDM, black, smooth.

Reinforcement: brasscoated steel, braided.

Cover: EPDM, red, fabric impression.

Temperature range:

Water: -40 °C to +120 °C, WP=60bar.

Saturated steam: +210 °C/18bar.

Superheated steam: +230 °C/18bar.

Electrical properties: conductive tube, $R < 10^6 \Omega / \text{lg}$.

STANDARD/APPROVAL

ISO 6134:2017 type 2 class A.

ISO

COUPLINGS/FITTINGS

Finger clamps, Boss type press couplings.

COMPLEMENTARY INFORMATION

Other lengths and dimensions available on request.



**OIL & GAS****S 2096**

ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE (STEAM) bar	WORKING PRESSURE (WATER) bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (.) or min. order m
19.0 ±0.5	7	33.0 ±1.0	18	60	180	190	0.77	20	5015502	1
19.0 ±0.5	7	33.0 ±1.0	18	60	180	190	0.77	40	5015503	1
19.0 ±0.5	7	33.0 ±1.0	18	60	180	190	0.77	60	5015504	1
25.0 ±0.5	7.5	40.0 ±1.0	18	60	180	250	1.06	20	5015506	480
25.0 ±0.5	7.5	40.0 ±1.0	18	60	180	250	1.06	40	5015507	480
25.0 ±0.5	7.5	40.0 ±1.0	18	60	180	250	1.06	60	5015508	480

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version

