

PROJECTOR 40



CONSTRUCTION & INFRASTRUCTURE

Spraying



APPLICATIONS

For spraying of mortar and mixed concrete as well as dry products.

Used as a service hose between pump and nozzle in transporting plaster, grout and ready mixed concrete.

ADVANTAGES

- Light weight, flexible and is easy to handle.
- Abrasion resistant tube compound.
- Conductive inner tube compound gives increased safety for the operator.

TECHNICAL DESCRIPTION

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: wear and weather resistant SBR, black, fabric impression.

Temperature range: -30°C to +70°C.


Electrical properties: conductive tube, $R < 2 \cdot 10^6 \Omega/m$.


Special properties: abrasion resistance of tube $< 40 \text{ mm}^3$ according to ISO 4649.



TRELLEBORG

PROJECTOR 40 WP 12 BAR



| CONSTRUCTION & INFRASTRUCTURE | | | PROJECTOR 40 | | |  | | | |
|---|-------------------------|-----------|----------------------------|-----------------------------|-------------------------|---|-------------|-------------------|---------------------------------|
| ID mm | WALL THICKNESS mm | OD mm | WORKING PRESSURE bar | BURSTING PRESSURE bar | BENDING RADIUS mm | WEIGHT kg/m | LENGTH m | ARTICLE NUMBER | STOCK () or min. order m |
| 25.0 | 9.5 ±0.50 | 44.0 ±1.0 | 12 | 40 | 120 | 1.2 | 40 | 59006811 | 120 |
| 32.0 | 10 ±0.50 | 52.0 ±1.0 | 12 | 40 | 150 | 1.57 | 40 | 59006812 | 1 |
| 40.0 | 10 ±0.50 | 60.0 ±1.0 | 12 | 40 | 180 | 1.8 | 20 | 59006813 | 1 |
| 40.0 | 10 ±0.50 | 60.0 ±1.0 | 12 | 40 | 180 | 1.8 | 40 | 59006814 | 1 |
| 50.0 | 10 ±0.75 | 70.0 ±1.5 | 12 | 40 | 250 | 2.22 | 20 | 59006815 | 1 |
| 50.0 | 10 ±0.75 | 70.0 ±1.5 | 12 | 40 | 250 | 2.22 | 40 | 59006816 | 1 |
| 60.0 | 10 ±0.75 | 80.0 ±1.5 | 12 | 40 | 290 | 2.3 | 20 | 59006817 | 480 |
| 60.0 | 10 ±0.75 | 80.0 ±1.5 | 12 | 40 | 290 | 2.3 | 40 | 59006818 | 1 |
| 63.0 | 13.5 ±0.75 | 90.0 ±1.5 | 12 | 40 | 340 | 2.83 | 20 | 59006949 | ∞ |
| 65.0 | 10 ±0.75 | 85.0 ±1.5 | 12 | 40 | 320 | 2.7 | 20 | 59006819 | 1 |
| 65.0 | 10 ±0.75 | 85.0 ±1.5 | 12 | 40 | 320 | 2.7 | 40 | 59006820 | 1 |
| Tolerance on length: ±1% (ISO 1307 Standard). | | | | | | | | | ∞ Upon availability. |

Digital version



WWW.TRELLEBORG.COM/FLUIDHANDLING