VULCAIN +

GENERAL INDUSTRY

Air and water



APPLICATIONS


For pneumatic tooling or pneumatic control lines (e.g. paint spray guns).

ADVANTAGES

- Static conductive tube.
- Very flexible hose especially at low temperatures.
- Suitable for hot water.

TECHNICAL DESCRIPTION

Inner tube: EPDM, black, smooth.
Reinforcement: synthetic textile.
Cover: EPDM, blue, smooth.
Temperature range: -40°C to +100°C.
Electrical properties: conductive tube, R<$10^6\Omega$/m.



GENERAL INDUSTRY | VULCAIN +



ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (ι) or min. order m
6.0 ±0.4	3	12.0 ±0.5	20	80	25	0.11	20	0129662	ι
6.0 ±0.4	3	12.0 ±0.5	20	80	25	0.11	40	0129663	ι
6.0 ±0.4	3	12.0 ±0.5	20	80	25	0.11	120	0129665	ι
7.0 ±0.5	3.5	14.0 ±0.6	20	80	25	0.15	20	0129667	ι
7.0 ±0.5	3.5	14.0 ±0.6	20	80	25	0.15	40	0129668	960
7.0 ±0.5	3.5	14.0 ±0.6	20	80	25	0.15	120	0129669	960
8.0 ±0.5	3.5	15.0 ±0.6	20	60	30	0.16	20	0129670	ι
8.0 ±0.5	3.5	15.0 ±0.6	20	60	30	0.16	40	0129671	ι
8.0 ±0.5	3.5	15.0 ±0.6	20	60	30	0.16	120	0129672	ι
9.0 ±0.5	3.5	16.0 ±0.6	20	60	35	0.18	20	0129673	ι
9.0 ±0.5	3.5	16.0 ±0.6	20	60	35	0.18	40	0129675	ι
9.0 ±0.5	3.5	16.0 ±0.6	20	60	35	0.18	120	0129676	3240
10.0 ±0.5	4	18.0 ±0.6	20	60	40	0.23	20	0129678	ι
10.0 ±0.5	4	18.0 ±0.6	20	60	40	0.23	40	0129679	ι
10.0 ±0.5	4	18.0 ±0.6	20	60	40	0.23	120	0129680	ι
12.0 ±0.6	4	20.0 ±0.7	20	60	60	0.26	20	5501021	¤
12.0 ±0.6	4	20.0 ±0.7	20	60	60	0.26	40	5501020	ι
12.0 ±0.6	4	20.0 ±0.7	20	60	60	0.26	120	5501019	2400

Tolerance on length: ±1% (ISO 1307 Standard). ¤ Upon availability.

Digital version

TRELLEBORG

WWW.TRELLEBORG.COM/FLUIDHANDLING