

PUMPADUKT L



OIL & GAS

Oil and petroleum
Suction and discharge for road and



APPLICATIONS

Suction and discharge of petroleum products with aromatics up to 50%.

Equipement of road tank trucks for oil and petrol deliveries and their loading/unloading bays.

ADVANTAGES

- 1 A highly light weight and flexible hose for easy handling. The corrugated cover allows extreme bendings.

TECHNICAL DESCRIPTION

Inner tube: oil and petrol resistant NBR, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: oil and weather resistant CR, black, corrugated, fabric impression.

Temperature range: -40°C to +100°C.

Electrical properties: conductive tube, $R < 10^6 \Omega / \text{lg}$.

STANDARD/APPROVAL

TRbF 131 Teil 2.



EN 1761.



and embossed: TRELLEBORG - PUMPADUKT L - NBR 1 - EN 1761:1999 - SD - ND - WP 10bar - Ω /T - month/year - batch number

**OIL & GAS****PUMPADUKT L**

| ID mm | WALL THICKNESS mm | OD mm | WORKING PRESSURE bar | BURSTING PRESSURE bar | MAX. VACUUM bar | BENDING RADIUS mm | WEIGHT kg/m | LENGTH m | ARTICLE NUMBER | STOCK () or min. order m |
|------------|-------------------------|------------|----------------------------|-----------------------------|-----------------------|-------------------------|----------------|-------------|-------------------|---------------------------------|
| 50.0 ±0.6 | 8 | 66.0 ±1.2 | 10 | 40 | 0.9 | 100 | 2.01 | 20 | 5013683 | 160 |
| 50.0 ±0.6 | 8 | 66.0 ±1.2 | 10 | 40 | 0.9 | 100 | 2.01 | 40 | 5013684 | 160 |
| 75.0 ±0.6 | 8 | 91.0 ±1.2 | 10 | 40 | 0.9 | 150 | 3.18 | 20 | 5013518 | ☒ |
| 75.0 ±0.6 | 8 | 91.0 ±1.2 | 10 | 40 | 0.9 | 150 | 3.18 | 40 | 5013519 | ☒ |
| 100.0 ±0.6 | 8 | 116.0 ±1.6 | 10 | 40 | 0.9 | 200 | 3.99 | 20 | 5013685 | 160 |
| 100.0 ±0.6 | 8 | 116.0 ±1.6 | 10 | 40 | 0.9 | 200 | 3.99 | 40 | 5013686 | 120 |

Tolerance on length: ±1% (ISO 1307 Standard).

☒ Upon availability.

Digital version

