

TEGUFLEX® P LPG



**CHEMICALS &
PHARMACEUTICALS**

Oil & Petroleum



APPLICATIONS

Liquefied Petroleum Gas (LPG)

ADVANTAGES

- ¹ Designed for 25 bar working pressure

TECHNICAL DESCRIPTION

Inner tube: HNBR, black, fluted.

Reinforcement: Aramid.

Cover: HNBR, black, smooth, oil and weather resistant.

Temperature range: -25 °C to 110 °C.

Max WP 25 bar at 90 °C

Max 110 °C at max WP 16 bar.

COUPLINGS/FITTINGS

BL = 130 mm

Turnable flanges in zinc plated carbon steel S235JR

Drilling PN40 according to EN 1092.

COMPLEMENTARY INFORMATION

Available for DN50 and DN80

PED (2014/68/EU)



TRELLEBORG IZARRA
IZARRA-ALAVA-SPAIN
Batch number - Working pressure - Testing pressure - T MAX/MIN - DN - Month/Year

CE 0056
MOD: H

TEGUFLEX LPG



TRELLEBORG

 CHEMICALS & PHARMACEUTICALS				TEGUFLEX® P LPG							
ID mm	PN	WORKING PRESSURE bar	BURSTING PRESSURE bar	BL m	COMPRESSIO N mm	ELONGATION mm	LATERAL mm	ANGULAR °	WITHOUT SUPPORT RING BAR	ARTICLE NUMBER	STOCK (1) or min. order piece
50.0	40	25	100	130	30	20	20	35	0.7	5603746	⌘
80.0	40	25	100	130	30	20	20	30	0.5	5603747	⌘
											⌘ Upon availability.

Digital version



WWW.TRELLEBORG.COM/FLUIDHANDLING