

GUTTELING CHEM 10 PS



CHEMICALS & PHARMACEUTICALS

Composite hoses
Chemical and corrosive products



APPLICATIONS

Suction and discharge of a large number of aggressive or corrosive chemicals, chemical waste and all petroleum products with aromatic content up to 100%.

For road and rail tanker equipment or fixed installations in the chemical industry.

ADVANTAGES

- ┆ Easy to handle due to hose flexibility (low bending radius).
- ┆ Usable at a wide range of temperatures.
- ┆ Capable of handling many different chemicals.

TECHNICAL DESCRIPTION

Internal helix: polypropylene coated steel.

Inner tube: polypropylene film.

Reinforcement: polypropylene layers.

Cover: PVC coated fabric, grey, corrugated.

External helix: stainless steel.

Temperature range: -30 °C to +100 °C.

Electrical properties: resistance between end fittings
≤100Ω/assembly.

STANDARD/APPROVAL

EN 13765: Bureau Veritas type approval
N° 7232905/8/049/TBE.



COUPLINGS/FITTINGS


All types of swaged couplings:



- standard or revolving Guillemin
- standard or secured camlock coupling
- threaded male or female fitting (BSP, NPT, etc.)
- fixed or swivel flange ISO PN10/16, PN20 (ASA150), TTMA, etc.

COMPLEMENTARY INFORMATION

Fitted lengths are delivered on request with pressure test certificate.

Imperial size on request.



 CHEMICALS & PHARMACEUTICALS		GUTTELING CHEM 10 PS				
ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	LENGTH m	ARTICLE NUMBER
65.0	78.5	10	40	200	30	30103720
80.0	95.0	10	40	280	30	30103748
100.0	118.0	10	40	400	30	30103830
Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).						

Digital version

