

VK 2000



GENERAL INDUSTRY

Exhaust and ventilation



APPLICATIONS

Extraction of air, smoke (also corrosive), dust and light particles.

Also used as cable protection.

ADVANTAGES

- ¹ A flexible PVC hose with a strong PVC spiral.
- ¹ Kink resistant.

TECHNICAL DESCRIPTION

Inner tube: PVCsmooth.

Reinforcement: impact resistant PVC helix.

Cover: PVC, blue, corrugated.

Temperature range: -10°C to +50°C.

Electrical properties: non conductive material.

 GENERAL INDUSTRY		VK 2000					
ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BENDING RADIUS mm	LENGTH m	ARTICLE NUMBER	STOCK (1) or min. order m
25.0	0.6	27.3	0.8	40	30	5109000	1
38.1	0.7	40.8	0.7	40	30	5109010	60
50.0	0.7	52.9	0.7	90	30	5109020	☒
63.5	0.7	66.9	0.6	100	30	5109025	60
76.2	0.7	79.9	0.5	120	30	5109030	1
90.0	0.8	94.1	0.4	150	30	5109035	☒
102.0	0.8	106.3	0.4	160	30	5109040	1
127.0	0.8	131.8	0.4	230	30	5109045	1
152.4	0.9	158.0	0.3	280	20	5109050	☒
Tolerance on length: ±1% (ISO 1307 Standard).							☒ Upon availability.

