

OIL 10 SD



OIL & GAS

Oil and petroleum

Suction and discharge applications



APPLICATIONS

Mineral and synthetic oil and household fuel suction and delivery hose (with aromatic content up to 50%).

Use not recommended for standard fuels and biofuels.

TECHNICAL DESCRIPTION


Inner tube: synthetic NBR rubber, black, smooth.



Reinforcement: synthetic textile with embedded steel helix.

Cover: synthetic NBR/SBR rubber, black, fabric impression.

Temperature range: -30 °C to +80 °C.

Electrical properties: conductive tube, $R < 10^6 \Omega/m$.



 OIL & GAS			OIL 10 SD						
ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK () or min. order m
19.0	29.0 ±1	10	30	0.9	80	0.51	40	5513629	1
51.0	64.0 ±1	10	30	0.9	200	1.64	40	5513633	1
76.0	90.0 ±1	10	30	0.9	320	2.71	40	5513635	1
152.0	172.0 ±1.2	10	30	0.9	610	7.82	40	5513638	1
Tolerance on length: ±1% (ISO 1307 Standard).									

