

# ABRA 10 SLURRY



## CONSTRUCTION & MINING EQUIPMENT

Abrasive materials hydraulic and pneumatic handling



### APPLICATIONS

Hydraulic suction and discharge of abrasive products.

### TECHNICAL DESCRIPTION

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: wear resistant NR/SBR, black, smooth fabric impression.

Temperature range: -30°C to +70°C.

Electrical properties: conductive tube,  $R < 1M\Omega/m$ .

### COUPLINGS/FITTINGS

Special half shelves coupling.

50-200mm



250-400mm





**CONSTRUCTION & MINING  
EQUIPMENT**

**ABRA 10 SLURRY**



ID mm	OD mm	TUBE THICKNESS mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
50.0	70.0	5	10	30	0.9	250	3	20	5513746	
75.0	96.0	5	10	30	0.9	375	4	20	5513747	
100.0	123.0	5	10	30	0.9	500	6	20	5513748	
125.0	150.0	5	10	30	0.9	650	7.5	20	5513749	
150.0	174.0	5	10	30	0.9	900	8	20	5513750	
200.0	230.0	6	10	30	0.9	1400	12	10	5513751	
250.0	282.0	6	5	15	0.9	1750	17	10	5513752	
300.0	336.0	8	5	15	0.9	2100	22	10	5513753	
350.0	386.0	8	5	15	0.9	2750	26	10	5513754	
400.0	436.0	8	5	15	0.9	3500	30	10	5513755	

Tolerance on length: ±1% (ISO 1307 Standard).



**TRELLEBORG**