

# ABRA 12



## BUILDINGS & CONSTRUCTION

Blasting, guniting



### APPLICATIONS

High abrasive resistant hose used for sandblasting (sand, steel shot, stone), spraying of mortar and mixed concrete as well as dry products (plaster, grout and ready mixed concrete).

### TECHNICAL DESCRIPTION

Inner tube: wear resistant NR, black, smooth.

Reinforcement: synthetic textile.

Cover: wear and weather resistant SBR, black, fabric impression.

Temperature range: -30°C to +80°C.


Electrical properties: conductive tube.

Special properties: abrasion resistance of tube <math>< 50\text{mm}^3</math> according to ISO 4649.



TRELLEBORG

ABRA 12





ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
13.0	27.0 ±1.2	12	36	104	0.5	40	5513728	
16.0	30.0 ±1.2	12	36	130	0.61	40	5513729	
19.0	33.0 ±1.2	12	36	160	0.71	40	5513730	
25.0	39.0 ±1.2	12	36	200	0.83	40	5513731	
32.0	48.0 ±1.2	12	36	260	1.17	40	5513732	
38.0	56.0 ±1.2	12	36	300	1.8	40	5513733	
51.0	71.0 ±1.2	12	36	410	2.22	40	5513734	
63.0	85.0 ±1.6	12	36	510	2.94	40	5513735	
76.0	100.0 ±1.6	12	36	610	3.73	40	5513736	

Tolerance on length: ±1% (ISO 1307 Standard).



TRELLEBORG