

AQUA 10 HOT



GENERAL INDUSTRY

Water
Discharge applications



APPLICATIONS

Hot water delivery hose used in industry, construction and agricultural applications.

TECHNICAL DESCRIPTION

Inner tube: high temperature resistant EPDM, black, smooth.

Reinforcement: synthetic textile.

Cover: high temperature resistant EPDM, black, fabric impression.


Temperature range: -30°C to +100°C.

HOT



TRELLEBORG

AQUA 10 HOT



 GENERAL INDUSTRY		AQUA 10 HOT						
ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (1) or min. order m
32.0	42.0 ±1	10	30	320	0.73	40	5503649	1
38.0	48.0 ±1	10	30	380	0.85	40	5503650	1
51.0	63.0 ±1	10	30	510	1.37	40	5503651	1
63.0	75.0 ±1	10	30	630	1.68	40	5503652	120
76.0	89.0 ±1.2	10	30	760	2.22	40	5503653	1
127.0	141.0 ±1.2	10	30	1270	3.7	40	5503646	1
152.0	168.0 ±1.2	10	30	1520	5.26	40	5503647	∅
Tolerance on length: ±1% (ISO 1307 Standard).								∅ Upon availability.

