MULTI 20

GENERAL INDUSTRY

Air and water



APPLICATIONS

Compressed air and water hose in industrial applications.

TECHNICAL DESCRIPTION

Inner tube: SBR, black, smooth.
Reinforcement: synthetic textile.
Cover: SBR, black, smooth.
Temperature range: -30°C to +70°C.



32-102mm



6-25mm

GENERAL INDUSTRY | **MULTI 20**



ID mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (ι) or min. order m
6.0	14.0	20	60	20	0.19	40	5513831	ι
8.0	16.0	20	60	30	0.23	40	5513832	ι
10.0	17.0	20	60	40	0.24	40	5513833	ι
13.0	22.0	20	60	55	0.38	40	5513834	ι
16.0	25.0	20	60	70	0.45	40	5513835	ι
19.0	29.0	20	60	80	0.58	20	5513836	ι
19.0	29.0	20	60	80	0.58	40	5513837	ι
25.0	36.0	20	60	100	0.82	40	5513838	ι
32.0	44.0	20	60	320	0.95	40	5513839	ι
38.0	52.0	20	60	380	1.2	40	5513840	ι
51.0	65.0	20	60	510	1.68	40	5513841	ι
63.0	79.0	20	60	630	2.34	40	5513842	ι
102.0	120.0	20	60	1020	4.14	40	5513844	¤

Tolerance on length: ±1% (ISO 1307 Standard). ¤ Upon availability.

TRELLEBORG