PROJECTOR 120 WHITE

CONSTRUCTION & INFRASTRUCTURE

Spraying



APPLICATIONS

For spraying of wet mortar, mixed concrete and other wet products.

Used as a service hose between pump and nozzle in transporting plaster, grout and ready mixed concrete.

ADVANTAGES


- High working pressure.
- Light weight, flexible and easy to handle.
- Abrasion resistant tube.
- Non-staining white cover avoids traces on walls and floors.

TECHNICAL DESCRIPTION

Inner tube: wear resistant NR, black, smooth.
Reinforcement: synthetic textile.
Cover: wear and weather resistant SBR, white, fabric impression.
Temperature range: -30°C to +70°C.
Electrical properties: antistatic tube.
Special properties: abrasion resistance of tube <40mm^3 according to ISO 4649.


COMPLEMENTARY INFORMATION

13.3m lengths available on request, min. order is three pieces and by multiple of three.
Other wall thickness and/or bursting pressure on request.



CONSTRUCTION & INFRASTRUCTURE

PROJECTOR 120 WHITE



ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK (l) or min. order m
25.0	7	39.0	40	120	200	0.85	40	59006807	l
35.0	7	49.0	40	120	280	1.13	40	59006808	200
50.0	9	68.0	40	120	410	2.22	20	59006809	l
50.0	9	68.0	40	120	410	2.22	40	59006810	l

Tolerance on length: ±1% (ISO 1307 Standard).

TRELLEBORG