

# AG 2100 MARINE CORRUGATED



## MARINE CONSTRUCTION & EQUIPMENT

Boat equipment  
Exhaust gas



### APPLICATIONS

Marine engine wet exhaust systems where the exhaust gases are mixed with the discharge of cooling water.

### ADVANTAGES

- | Extreme flexibility.
- | Low weight.
- | Weather and ageing resistant.
- | Corrugated and user friendly.
- | DNV approved.

### TECHNICAL DESCRIPTION

Inner tube: CR, black, smooth.

Reinforcement: synthetic textile with steel wire embedded helix.

Cover: CR, black, fabric impression, corrugated.

Temperature range: -30°C to +100°C.  
Can intermittent withstand +580°C.

### COUPLINGS/FITTINGS

Clamps.

### COMPLEMENTARY INFORMATION

Certified by DNV in accordance to ISO 13363 type 2, SAE J 2006 type R2, Nordic Boat Standard MC9.  
Other dimensions available on request.



**MARINE CONSTRUCTION & EQUIPMENT****AG 2100 MARINE CORRUGATED**

ID mm	WALL THICKNESS mm	OD mm	WORKING PRESSURE bar	BURSTING PRESSURE bar	MAX. VACUUM bar	BENDING RADIUS mm	WEIGHT kg/m	LENGTH m	ARTICLE NUMBER	STOCK ( ) or min. order m
76.0	5 ±0.6	86.0 ±1.2	5	15	0.9	175	1.81	20	5500796	40
76.0	5 ±0.6	86.0 ±1.2	5	15	0.9	175	1.81	40	0071151	40
90.0	5 ±0.7	100.0 ±1.3	5	15	0.9	200	2.16	20	0071152	40
90.0	5 ±0.7	100.0 ±1.3	5	15	0.9	200	2.16	40	5500797	40
102.0	5 ±0.7	112.0 ±1.3	5	15	0.9	220	2.42	20	0071153	80
102.0	5 ±0.7	112.0 ±1.3	5	15	0.9	220	2.42	40	5500798	80
127.0	5.5 ±0.7	138.0 ±1.4	4	12	0.9	250	2.97	20	0071154	80
127.0	5.5 ±0.7	138.0 ±1.4	4	12	0.9	250	2.97	40	5500799	80
152.0	5.5 ±0.7	163.0 ±1.4	4	12	0.9	350	3.52	20	0071155	40
205.0	6.5 ±1.0	217.0 ±2.0	4	12	0.8	590	6	20	5014028	20

Tolerance on length: ±1% (ISO 1307 Standard).

Digital version

**TRELLEBORG**[WWW.TRELLEBORG.COM/FLUIDHANDLING](http://WWW.TRELLEBORG.COM/FLUIDHANDLING)